

Data Sheet

DSTC/SSTC

Tooth Plate Connectors

Designed to improve the performance of bolted connections, timber connectors are manufactured in accordance with BS EN 912:200 Type C6/C7 and produced from 1mm thick galvanised steel to BS EN 10346:2009 DX51D +G275.

Manufactured from hot rolled steel to BS EN 10025. Stainless steel to BS 1449 and hot dipped galvanised after manufacture to BS EN ISO 1461: 1999 are also available.



Product Reference	Size	Box Qty.
SSTC/38	38mm dia./ single sided / M12	100
DSTC/38	38mm dia./ double sided / M12	100
SSTC/50	50mm dia./ single sided / M12	100
DSTC/50	50mm dia./ double sided / M12	100
SSTC/63	63mm dia./ single sided / M12	100
DSTC/63	63mm dia./ double sided / M12	100
SSTC/75	75mm dia./ single sided / M12	100
DSTC/75	75mm dia./ double sided / M12	100

Special hole sizes are available to order.



To order or find out more call **01924 364 794** or scan the QR code.

PRODUCT CODE	SIZE	BOLT HOLE SIZE	NAIL HOLE SIZE	THICKNESS
DSTC/38	38mm	10.5mm	2 x 3mm	.9mm
DSTC/50	50mm	12mm	2 x 3mm	.9mm
DSTC/63	63mm	14mm	2 x 3.75mm	1.2mm
DSTC/75	75mm	14mm	2 x 3.75mm	1.2mm
DSTC/50/P	50mm	12mm	2 x 3mm	.9mm

DSTC/50/P = DOUBLE SIDED TIMBER CONNECTOR 10 PER BAG

MANUFACTURED FROM PRE GALVANISED STEEL TO BS EN 10346 (2009) DX51D (G275)

BPC Building Products Ltd, Flanshaw Way, Wakefield

MATL	MILD STEEL	UNSPEC TOLS	UNSPEC	SCALE	DATE 18/7/11	CHECKED	DATE
DESCRIPTION	DOUBLE SIDED TIMBER CONNECTOR		PRODUCT CODE	DSTC/SIZE			
DRAWING NO 099							

PRODUCT CODE	SIZE	BOLT HOLE SIZE	NAIL HOLE SIZE	THICKNESS
SSTC/38	38mm	10.5mm	2 x 3mm	.9mm
SSTC/50	50mm	13mm	2 x 3mm	.9mm
SSTC/63	63mm	13mm	2 x 3.75mm	1.2mm
SSTC/75	75mm	14mm	2 x 4mm	1.2mm

**MANUFACTURED FROM PRE GALVANISED STEEL TO
BS EN 10346 (2009) DX51D (G275)**

BPC Building Products Ltd, Flanshaw Way, Wakefield					
MATL	MILD STEEL	UNSPEC TOLS	DIMS	SCALE	DRAWN MJS
			MM		DATE 21/7/11
DESCRIPTION	SINGLE SIDED TIMBER CONNECTOR		PRODUCT CODE	SS/TC/SIZE	
				DRAWING NO 0113	