


## Data Sheet MTH/CF

### Concealed Flange Multi-Truss Hanger

Special Multi Truss Hanger with concealed fixing flanges available 100mm wide and above.

Product Reference	Width(W)	Box Qty.
MTH/CF/380	100mm only	50
MTH/CF/500	100/125/150mm	25
MTH/CF/560	100/125/150mm	25
MTH/CF/620	100/125/150mm	25



Special non-standard widths available to order.

For use in heavy duty applications such as multiple truss units, main trimmer joists, purlin to beam connections or similar situations where unusually heavy loads occur. Manufactured from 2mm thick galvanised steel. Bolt hole to suit M12 fixing, nail holes 5mm diameter.

Produced from galvanised steel to BS EN 10346:2009 + G275 as standard. Use 30 x 3.75mm sheradised square twisted nails in all pre-punched holes, together with bolts in Multi Truss Hanger range where required. Stainless steel hangers are available to order. Bearing surface on all multi-truss hangers is 75mm.

PRODUCT CODE	WIDTH	BOLT HOLES	NAIL HOLES
MTH/CF/380	100	4	32
MTH/CF/500	100 125 150	6	50
MTH/CF/560	100 125 150	6	50
MTH/CF/620	100 125 150	8	66

PRODUCT CODE	LENGTH
MTH/CF/380/100	140
MTH/CF/500/100	200
MTH/CF/500/125	187.5
MTH/CF/500/150	175
MTH/CF/560/100	230
MTH/CF/560/125	217.5
MTH/CF/560/150	205
MTH/CF/620/100	280
MTH/CF/620/125	247.5
MTH/CF/620/150	235

**MINIMUM JOIST WIDTH 100mm**

**MANUFACTURED FROM 2mm GALVANISED STEEL TO BS EN 10346 (2009) DX51D (G275)**

**USE CORRECT NO OF 12mm BZP HT BOLTS IN BOLT HOLES  
USE SHERADISED SQUARE TWIST NAILS IN ALL NAIL HOLES  
TO ACHIEVE SWL**

**BPC Building Products Ltd, Flanshaw Way, Wakefield**

MATL 2mm GALVANISED MILD STEEL	UNSPEC TOLS	DIMS mm	SCALE	DRAWN MJS DATE 13/7/11	CHECKED DATE
DESCRIPTION CONCEALED FLANGE MULTI-TRUSS HANGER		PRODUCT CODE MTH/CF/ SIZE		DRAWING NO 086	